



NOTES:

- 1) FIBER-PureWave® XL55 OR SL55
- 2) RANDOMIZED
- 3) MIN. BEND RADIUS-2"

PART NUMBER	LENGTH	REV
FTIIG16861-12	12"	A
FTIIG16861-40	40"	A
FTIIG16861-60	60"	A
FTIIG16861-96	96"	A
FTIIG16861-240	240"	A

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FIBEROPTICS TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FIBEROPTICS TECHNOLOGY IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±2° TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	DRAWN	MH 04/17/2020
	CHECKED	SG 07/10/2020
	ENG APPR.	SG 08/07/2020
	MFG APPR.	
INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.	
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

FIBEROPTICS TECHNOLOGY		
TITLE: ϕ .500		
MACHINE VISION LIGHT GUIDE		
SIZE	DWG. NO.	REV
A	SEE CHART	SEE CHART
SCALE: 1:2		SHEET 1 OF 1